





## Epson **9880** Stylus Pro

Set new standards in A0+/B0+ colour and black & white printing

Add quality and productivity to in-house production printing up to 44" wide. Enhance performance in proofing, photography and even fine art with Epson UltraChrome<sup>™</sup> K3 ink and Vivid Magenta technology.

## Key benefits:

- The highest quality A0+ (44") 8-colour production printer
- Epson UltraChrome K3 ink with Vivid Magenta for superb colour
- Neutral black & white and perfectly balanced greyscale
- Improved productivity due to high speed and a wide media choice

Produce superb, contract quality colour and black & white with a single printer. See the difference with Epson UltraChrome K3 ink with Vivid Magenta, an 8-colour ink set with three black inks and improved image-processing technology.

Combine outstanding, repeatable, long lasting results with improved productivity. The printer features new printer drivers, a wide media choice and has both the speed to improve throughput and the reliability for overnight printing.

Ideal for proofing, photography and fine art – get contract quality results for demanding applications

Outstanding colour and black & white printing – achieve superb image quality, high colour stability and maximum tonal gradation Advanced 8-colour ink set – Epson UltraChrome K3 8-colour ink set with Vivid Magenta and three black inks

Enhanced image processing technology – extended colour representation of reds and blues

Photo realistic quality that lasts – impressive lightfastness for consistent, repeatable quality

**Versatile media handling** – choose from an extensive range of matte, gloss and fine art finishes

**Improved productivity** – fast print speeds and high capacity ink cartridges for overnight printing

**Simple operation** – customise, share and memorise settings with new printer drivers

Epson Stylus Pro 9880			
Size	44" (A0+ / B0+) Epson Micro Piezo™ drop-on-demand inkjet technology Epson Variable-sized Droplet Technology and 3.5 pl Epson Ultra Micro Dot™		
Print technology		pson Variable-sized Droplet Technology and 3.5 pl Epson Ultra Micro Dot™ rint head configuration: 180 nozzles x 8 colours	
late as a feature	6		
Ink system	9 colour pigmented ink (C, VM, Y, LC, VLM, LK, LLK, Photo K, Matte K) with CSIC with 8 slots (one slot for interchangable Matte K and Photo K)		
			nge between Matte K and
	Photo K are delivered wi		ige between Matte K and
Resolution	2880 x 1440 dpi Bi-Directional, Epson Variable-sized Droplet Technology		
Speed	Up to 22.1 m <sup>2</sup> / Hr (B0+ / Plain paper / Draft mode)		
Driver			
Interfaces	Standard: USB 2.0 (com	ft <sup>®</sup> Windows 2000, XP, XP 64-bit, Vista, MAC OS <sup>®</sup> X 10.x.x	
Roll dimensions	Core diameter 2" or 3".	2000, XP, XP 64-bit, Vista, MAC OS®X 10.x.x ompatible with 1.1), Ethernet 10 / 100Mb	
Paper handling			
Roll media		or 3''. Max. outside diameter Φ150 mm : 150 mm / outside diameter)	
	Media width 203.2 mm	•	)
	Minimum media length 2 Media thickness 0.08 mi		
Cut sheet	Manual insertion feeder		m
Cut sheet			
	Media width size A4 / LTR – A0+ / 44" (210 mm - Media thickness 0.08 mm – 1.50 mm		
Print margins			
Roll media	3 modes available; mode	e 1: 3 mm on all edges	s (top, sides, bottom);
	mode 2: 15 mm (top an	,, (	les);
	mode 3: 15 mm (top, si	, ,	
Sheet media	2 modes available; mode	<b>( )</b> <i>)</i>	
Edge to odge / Porderlage	mode 2: 3 mm (top and sides) 14 mm (bottom)		
Edge-to-edge / Borderless			
Poll media / Cut cheet	Both edge-to-edge and	full bleed for the follow	wing media widths: 10" 13" 14" 16" 17"
Roll media / Cut sheet			wing media widths: 10'', 13'', 14'', 16'', 17", 4 mm
Roll media / Cut sheet	515 mm, 594 mm, 609.	.6 mm, 728 mm, 914.	.4 mm
Roll media / Cut sheet Ink cartridges		.6 mm, 728 mm, 914. can be automatically c	.4 mm sut to any length
	515 mm, 594 mm, 609 Top and bottom edges of 110 and 220 ml ink cap	.6 mm, 728 mm, 914. can be automatically c acity, single size pack	.4 mm sut to any length
	515 mm, 594 mm, 609 Top and bottom edges of 110 and 220 ml ink cap	.6 mm, 728 mm, 914. can be automatically c acity, single size pack	.4 mm cut to any length aging < level control even on re-inserted cartridges 220 ml
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black	.6 mm, 728 mm, 914. can be automatically c acity, single size pack artridge system for ink 110 ml C13T611800	.4 mm cut to any length aging < level control even on re-inserted cartridges 220 ml C13T612800
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black	.6 mm, 728 mm, 914. can be automatically of acity, single size pack artridge system for ink 110 ml C13T611800 C13T602100	.4 mm sut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black	.6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700	.4 mm sut to any length aging (level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Light black	6 mm, 728 mm, 914. can be automatically c acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900	.4 mm cut to any length aging (level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603900
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Light light black Cyan	6 mm, 728 mm, 914. can be automatically c acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200	.4 mm cut to any length aging (level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603900 C13T603200
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Light black Cyan Vivid magenta	.6 mm, 728 mm, 914. can be automatically c acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300	.4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603900 C13T603200 C13T603300
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Cyan Vivid magenta Yellow	.6 mm, 728 mm, 914. can be automatically of acity, single size pack artridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300 C13T602400	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603900 C13T603200 C13T603300 C13T603300 C13T603400
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta	.6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602200 C13T602200 C13T602200 C13T602300 C13T602400 C13T602400	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Cyan Vivid magenta Yellow	6 mm, 728 mm, 914. can be automatically c acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602200 C13T602200 C13T602200 C13T602300 C13T602400 C13T602400 C13T602500	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603900 C13T603200 C13T603300 C13T603300 C13T603400
	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T6011800 C13T602100 C13T602900 C13T602900 C13T602900 C13T602200 C13T602400 C13T602400 C13T602500 ar prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Photo black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T6011800 C13T602100 C13T602900 C13T602900 C13T602900 C13T602200 C13T602400 C13T602400 C13T602500 ar prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH)	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years f 1702 x 678 x 1196 mm	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300 C13T602400 C13T602600 C13T602500 ir prints for B&W prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years for 1702 x 678 x 1196 mm Approx. 90 kg without in	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300 C13T602400 C13T602600 C13T602500 ir prints for B&W prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight Noise level	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years for 1702 x 678 x 1196 mm Approx. 90 kg without in Approx. 50 dB	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300 C13T602400 C13T602600 C13T602500 ir prints for B&W prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years for 1702 x 678 x 1196 mm Approx. 90 kg without in Approx. 50 dB Printing: 50 W or less	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300 C13T602400 C13T602600 C13T602500 ir prints for B&W prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight Noise level	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Light black Cyan Vivid light magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years for 1702 x 678 x 1196 mm Approx. 90 kg without in Approx. 50 dB Printing: 50 W or less Standby: 6 W or less	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300 C13T602400 C13T602600 C13T602500 ir prints for B&W prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight Noise level Power consumption	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years ff 1702 x 678 x 1196 mm Approx. 90 kg without in Approx. 50 dB Printing: 50 W or less Standby: 6 W or less Power off: 1 W or less	6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602300 C13T602400 C13T602600 C13T602500 ir prints for B&W prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight Noise level	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colot In excess of 100 years for 1702 x 678 x 1196 mm Approx. 90 kg without in Approx. 50 dB Printing: 50 W or less Standby: 6 W or less Power off: 1 W or less 1 year on-site repair	.6 mm, 728 mm, 914. can be automatically of acity, single size pack intridge system for ink 110 ml C13T611800 C13T602100 C13T602700 C13T602200 C13T602200 C13T602200 C13T602300 C13T602400 C13T602500 ar prints for B&W prints	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight Noise level Power consumption	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years ff 1702 x 678 x 1196 mm Approx. 90 kg without in Approx. 50 dB Printing: 50 W or less Standby: 6 W or less Power off: 1 W or less	6 mm, 728 mm, 914. can be automatically of acity, single size pack 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602200 C13T602400 C13T602500 ur prints for B&W prints hk and media	4 mm cut to any length aging ( level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603200 C13T603400 C13T603600
Ink cartridges Lightfastness General Dimensions (WxDxH) Weight Noise level Power consumption Warranty	515 mm, 594 mm, 609. Top and bottom edges of 110 and 220 ml ink cap Pressurised, Intellidge ca Matte black Light black Light black Light light black Cyan Vivid magenta Yellow Vivid light magenta Light cyan Up to 75 years for colou In excess of 100 years for 1702 x 678 x 1196 mm Approx. 90 kg without in Approx. 50 dB Printing: 50 W or less Standby: 6 W or less Power off: 1 W or less 1 year on-site repair Optional extension to 3	6 mm, 728 mm, 914. can be automatically of acity, single size pack 110 ml C13T611800 C13T602100 C13T602700 C13T602900 C13T602200 C13T602200 C13T602200 C13T602400 C13T602500 ur prints for B&W prints hk and media	4 mm sut to any length aging (level control even on re-inserted cartridges 220 ml C13T612800 C13T603100 C13T603700 C13T603700 C13T603200 C13T603200 C13T603300 C13T603400 C13T603500



Telephone: 08702 416900 (UK) 1 800 409132 (Republic of Ireland) E-mail: info@epson.co.uk

www.epson.co.uk www.epson.ie Fax: +44 (0) 8702 413093



EPSON® is a registered trademark of Seiko EPSON® Corporation. All other product names and other company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice.